



PRESSURE TREATED TIMBER
WITH BUILT-IN COLOUR



PRESSURE TREATED TIMBER



TANATONE
END GRAIN PRESERVATIVE



TANALISED
END GRAIN PRESERVATIVE

DESCRIPTION & APPEARANCE

ENSELE TANALISED and ENSELE TANATONE are brush-on, water based end grain timber preservatives based on triazole technology. They are designed for the re-treatment of exposed cross-cut, notched or drilled surfaces of TANALITH and TANATONE pressure treated timbers and help maintain the integrity of the pressure treated timber against fungal and insect attack.

ENSELE TANALISED is a thickened liquid with little perceptible odour. It is for use with TANALISED pressure treated timbers that have an initial green colouration.

ENSELE TANATONE is a thickened liquid with little perceptible odour. It is for use with TANATONE pressure treated timbers that have an initial brown colouration.

Once applied the product will gradually blend into the colour of the preservative treated timber.

Supplied in sturdy, re-sealable metal cans in both 1kg and 5kg sizes, the products are easy to brush apply.

Both products are approved under the Biocidal Products Regulations and by relevant national authorities for both professional and non professional use.

USES

Whenever TANALITH or TANATONE pressure treated timber is cross-cut, notched or drilled on-site, the exposed surfaces must be re-treated with ENSELE TANALISED or ENSELE TANATONE end-grain preservative to maintain the integrity of the protective system.

APPLICATION

Stir well before and during use. Use undiluted, liberally swabbing areas exposed by crosscutting, holes or notches. Apply by brush directly.

Coating should be wiped from 'show faces' with a damp cloth before drying.

NUMBER OF COATS

Two liberal coats. Allow time to dry along the grain of the timber before applying the second coat.

BRUSH CLEANING

Remove as much product as possible from the brush before washing with water. Please do not pour unused product or brush washings down the drain, dispose of in accordance with local waste regulations.

SHELF LIFE

The product has a shelf life of 18 months in original sealed cans, when stored away from extremes of temperature. Protect product from freezing. Once opened use within 6 months.

SAFETY NOTE

A material safety data sheet is available upon request at the contact details below.

Always read the label. Use wood preservatives safely. Do not allow product to enter drains and watercourses.

FURTHER INFORMATION

For further information please contact Arch Timber Protection Customer Services at the address below.



Wheldon Road, Castleford, West Yorkshire, WF10 2JT.

Tel: +44 (0)1977 714000 Fax: +44 (0)1977 714001

E-Mail: timberprotectionadvice.ukca@lonza.com www.archtimberprotection.com

IN CASE OF EMERGENCY TELEPHONE 01235 239670 (24 hours).

© Copyright 2014 Arch Timber Protection.

™ ENSELE, TANALISED, TANATONE and TANALITH are registered trademarks of Arch Timber Protection, a Lonza company.

Disclaimer: Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, Arch Timber Protection gives no undertaking to that effect and no responsibility can be accepted for reliance on this information.

Arch Timber Protection updates its literature as and when necessary. Please ensure you have an up to date copy.
Arch Timber Protection is a Lonza company.